

<b>MAG LIFE</b>	<b>#9-15 HWH SHEET TO WOOD W/ SEALER</b>
<b>VERY SHARP POINT</b>	
<b>#9-15 LENGTHS 1, 1 1/2, 2, 2 1/2, 3</b>	



1/4" Hex Drive



25RAHC/LONG

**PHYSICAL PROPERTIES**

<b>Head Across Flats :</b>	.250—.244	<b>Minimum Tensile :</b>	1500 Pounds
<b>Thread Diameter O.D.</b>	.179—.174	<b>Minimum Torque :</b>	39 Inch Pounds
<b>Thread Diameter I.D.</b>	.118—.113	<b>Minimum Shear:</b>	933 Pounds

**PULL OUT STRENGTH—ULTIMATE POUNDS**

MATERIAL TESTED	SPRUCE	FIR	OAK	PINE
<b>PENETRATION</b>	<b>1"</b>	<b>1"</b>	<b>1"</b>	<b>1"</b>
<b>AVE. PULL OUT</b>	<b>710</b>	<b>825</b>	<b>1130</b>	<b>1170</b>

**PULL OVER STRENGTH—ULTIMATE POUNDS**

WASHER DIAMETER	STEEL SHEETING	
	<b>26 GAUGE</b>	<b>29 GAUGE</b>
<b>1/2"</b>	<b>572</b>	<b>473</b>

**RECOMMENDED DRIVING TOOLS**

2000—2500 RPM variable speed electric screw gun equipped with depth locating nose piece to prevent overdriving and strip out. (Do not use impact type drivers.)

This data is the result of test performed under laboratory conditions. The data is provided only as a guide as results may vary under actual assembly conditions.