

## #14 Type "17" Sheet to Wood

- The DB #14 Type "17" Sheet to Wood Slotted sharp point will quickly and consistently pierce into 20 to 29 gauge steel sheeting and then into wood without slipping or damaging the panel. The DB #14 Type "17" Sheet to Wood is available in lengths from 1" to 2" and is available with DB's MAG Life Coating.



5/16" HEX DRIVE



SIZE	HEAD SIZE	POINT	THREAD LENGTH	PCS / CTN	LBS / CNT
#14 X 1"	5/16"	17	FULL	3000	42
#14 X 1-1/2"	5/16"	17	FULL	2000	34
#14 X 2"	5/16"	17	FULL	1500	27

SPECIFICATIONS			
HEAD ACROSS FLATS:	.305 - .312	MINIMUM TENSILE:	3500 POUNDS
THREAD DIAMETER: (O.D.)	.248 - .254	MINIMUM TORSION:	125 INCH POUNDS
THREAD DIAMETER: (I.D)	.178 - .185	MINIMUM SHEAR:	2400 POUNDS

### REQUIRED DRIVING TOOLS

2000—2500 RPM variable speed electric screw gun equipped with depth locating nose piece to prevent overdriving and strip out. (**Do not use impact type drivers.**)

## PULL OUT VALUES

FASTENER	WOOD TYPE AND THICKNESS	
	POINT	PINE
DIAMETER		
#14	17	1013
PENETRATION	-	1"

This data is the result of test performed under laboratory conditions. The data is provided only as a guide as results may vary under actual assembly conditions.