



Installation Guidelines

The following 5 installation guidelines were developed over years of application issues from our customers. While not all of the issues will be addressed by these 5 guidelines a majority of them will. By instructing your installation crew to follow these 5 installation guidelines a majority of issues will be avoided.

- 1) Correct Torque of Screw Gun
- 2) Correct Angle of Fastener
- 3) Proper Screw Gun
- 4) Proper Extension Cord
- 5) Light Pressure on fastener

1) Correct Torque

Proper use of the screw gun can greatly reduce fasteners being over driven or under driven. Step one is to purchase the correct screw gun. Step two is to properly set the clutch or nose piece of the screw gun.

This is the number one installation error on the job.

Driven Correctly

	One Piece Fasteners		Two Piece Fasteners
Sealing Material is only slightly visible. Washer is weather tight.		Correct	

Over Driven

Sealing Material is extruded far from metal washer edge. Metal Washer is deformed. Washer is cut or ripped. Fastener may also break.		Incorrect	
--	--	-----------	--

Under Driven

Sealing washer not compressed. Assembly is loose.		Incorrect	
---	--	-----------	--

2) Correct Angle

Fastener must be installed perpendicular to the panel. Being off for more than a few degrees can lead to washer leakage or premature washer degradation.

	One Piece Fasteners		Two Piece Fasteners
Fastener drilled perpendicular to panel. Washer is weather tight		Correct	
Fastener drilled off angle to panel. Washer material is off to one side. Washer is cut or ripped.		Incorrect	



Installation Guidelines Continued

3) Proper Screw Gun

Standard 2000 to 2500 RPM variable speed screw guns with 5 to 8 amps and a positive clutch and or depth locating nose piece are recommended. DO NOT USE IMPACT TYPE GUNS OR 4,000 RPM DRYWALL GUNS

DB recommends and sales the following quality Dewalt Screw Guns

Dewalt DW 268



Features:

- Helical-cut steel, heat-treated steel gears for long life and durability
- High power motor for metal fastening applications
- **Versa-Clutch® torque adjustment system "dials in" the proper torque needed to efficiently drive fasteners without stripping or breaking fastener**
- Rubber grip and two-finger trigger for increased comfort and greater control
- Metal nose and gear case for durability on the job
- Excellent ergonomics offers less user fatigue

SPECIFICATIONS

Amps	6.5 Amps
No Load Speed	0-2,500 rpm
Clutch	Versa-Clutch®
Torque	132 in-lbs
Max Fastener Size	#14
Tool Weight	3.7 lbs

Dewalt DW 266



Features:

- Ideal for use with TEKS® screws*
- Helical-cut steel, heat-treated steel gears for long life and durability
- Metal gear housing for jobsite durability and increased reliability
- **Depth-sensitive, "set and forget" nosepiece for consistent fastener depth**
- Rubber grip and two-finger trigger for increased comfort and greater control

SPECIFICATIONS

Amps	6.5 Amps
No Load Speed	0-2,500 rpm
Clutch	Standard
Torque	132 in-lbs
Max Fastener Size	#14
Tool Weight	3.5 lbs



DB BUILDING FASTENERS

5555 E. Gibraltar St
Ontario CA 91764
www.selfdrillers.com

Ph (909) 581 6740
Fax (909) 581 6745

Installation Guidelines Continued

4) Proper Extension Cord

For every foot of extension cord a percentage of voltage is lost. Proper extension cord gauge is essential for the screw gun to work properly. The following chart shows the proper gauge of the extension cord.

Rated Amp for Gun	Extension cord length				
	25'	50'	75'	100'	150'+
up to 5	16	16	16	14	12
5.1 to 8.0	16	16	14	12	10

5) Do not force the fastener.

Apply only enough pressure to allow the drill point to cut efficiently. Over assertion can make drill point break or over heat and melt. Applying too much pressure not only can flaw the install of the fasteners but can also cause undue strain and exhaustion of installer.

One also asserts too much pressure when installing sheeting through a gap of insulation or air space and onto the substrate. This requires the fastener to thread the upper sheet and drill the lower sheet, purlin or other substrate at the same time. While the fastener is threading the upper sheet the point of the fastener is forced into the lower substrate. This force is strong enough (especially in decking applications) to break the fastener point at the substrate.

As a rule of thumb the thicker the material the slower the speed the installer should use. When installing into 12 gauge purlins max 2,500 rpm's can be used. When installing into 1/4" steel using a 4.5 self driller or 1/2" steel using a 5 point 1,000 to 1,800 rpm's is recommended.

Sacramento Service Center

8185 Belvedere Ave
Suite B
Sacramento CA 95826

Ph (916) 504-4245
Fax (916) 504-4246

Laredo Service Center

14213 Business Ave.
Laredo TX 78045

DB Building Fasteners is a proud distributor of the following manufacturers:

