

#9 HWH Self-Piercing Screw

Designed to pierce up to 22ga sheet metal into wood substrates.

- 1/4" Hex Drive
- Sharp Point
- #9-15 Twin-Lead Thread Pattern - Fully Threaded
- Longlife Coated - 1,000 Hours Without Red Rust Per ASTM B117
- Assembled to G90 Galvanized 15/32"OD Black EPDM Bonded Sealing Washers
- Custom Head Painting Available for Exact Color Match



Part Number	Length
9N100SHBT/WG	1"
9N150SHBT/WG	1-1/2"
9N200SHBT/WG	2"
9N250SHBT/WG	2-1/2"
9N300SHBT/WG	3"

Tensile (lbs. min.)	1750
Shear (avg. lbs. ult.)	1223
Torsional (min. in .lbs.)	60

Pull-Out Values	19/32" OSB	23/32" OSB	1/2" PLY	5/8" PLY	3/4" PLY	2" X 4" Douglas Fir
#9-15	244#	318#	274#	392#	407#	953#
Penetration	through	through	through	through	through	1-1/4" embedment

Installation:

Install with a 0-2,500 RPM screw gun equipped with a clutch or depth sensitive nose piece.

DO NOT USE IMPACT TOOLS.

Disclaimer: All test results and recommendations are based on laboratory tests. Actual jobsite conditions and field values may vary, therefore we assume no liability for use of this information. This document is subject to revision. We reserve the right to make technical changes.